







Цена листа валидна от 01.01.2023 г.


### TWO-WIRE IP VIDEO INTERCOM

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
C313W-2		<p><b>2-wire SIP Indoor unit (Linux Version)</b></p> <ol style="list-style-type: none"> <li>7" capacitive touch screen with energy saving mode</li> <li>Reception of a HD picture from the door communicator</li> <li>Two-way communication based on SIP v2.0 protocol</li> <li>Powered by Akuvox NS-2 or external source</li> <li>Supports US or European electrical wall box mounting</li> <li>Bluetooth, and Wireless feature</li> <li>Support connecting with R20A-2 or NS-2 through 2-wire cable</li> </ol>	20	US\$180	342.00
R20A-2		<p><b>2-wire SIP Intercom with one Button (Video &amp; Card reader)</b></p> <ol style="list-style-type: none"> <li>Body material: Zinc alloy</li> <li>Camera: 2M pixels, automatic lighting, Viewing angle: 110° (H) / 58° (V)</li> <li>RF Card Reader 13.56MHZ&amp;125KHZ Card reader</li> <li>Output Relay: 2 output relays for door opener</li> <li>Water-proof &amp; Dust-proof: IP65</li> <li>Installation: Surface Mount model</li> <li>Powered by Akuvox NS-2 or C313W-2</li> <li>Two-way audio communication over IP networks with Echo Cancel</li> <li>Support connecting with C313W-2 or NS-2 through 2-wire cable</li> </ol>	20	US\$257	488.30
NS-2		<p><b>2-wire IP Network Switch</b></p> <ol style="list-style-type: none"> <li>Connects up to 6 2-wire IP intercom devices;</li> <li>Support network and power supply for R20A-2 or C313W-2 through 2-wire cable</li> <li>Support multi-level cascade through 2-wire cable</li> <li>Powerd by 48VDC power supply</li> <li>Installation:Rail mounting</li> </ol>		US\$143	271.70
HDR-60-SPEC		<p><b>Power Supply Unit for 2-wire IP Intercom</b></p> <ol style="list-style-type: none"> <li>100~240 VAC Input, 48VDC/1.25A Output</li> <li>Installation:Rail mounting</li> </ol>		US\$49	93.10
2-wire IP Intercom Kit (Coming Soon)		<p><b>2-wire IP Intercom Kit</b></p> <p>Including:</p> <ol style="list-style-type: none"> <li>1 pcs of C313W-2</li> <li>1 pcs of R20A-2</li> <li>1 pcs of 48V Power Supply Unit</li> <li>4 pcs of Free Smartplus Accounts</li> </ol>		US\$486	923.40


R20K-2 (On Wall)		<p><b>2-wire SIP Intercom with Keypad and RF card reader</b></p> <p>1.Front panel:Aluminum alloy  2.Output Relay: 2 output relays for door opener  3.Water-proof &amp; Dust-proof: IP65  4.Wide-angle camera: 120o  5.Two-way video communication over IP networks with Echo Cancel  6.Complies with SIP standard for easy integration in every SIP PBX  <b>7. Support connecting with C313W-2 or NS-2 through 2-wire cable</b>  <b>8. Installation: Surface Mount</b></p>	20	US\$357	678.30
R20K-2 (In Wall)		<p><b>2-wire SIP Intercom with Keypad and RF card reader</b></p> <p>1.Front panel:Aluminum alloy  2.Output Relay: 2 output relays for door opener  3.Water-proof &amp; Dust-proof: IP65  4.Wide-angle camera: 120o  5.Two-way video communication over IP networks with Echo Cancel  6.Complies with SIP standard for easy integration in every SIP PBX  <b>7. Support connecting with C313W-2 or NS-2 through 2-wire cable</b>  <b>8. Installation: Flush Mount</b></p>	20	US\$400	760.00



#### SIP DOOR PHONE

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
E12S		<p><b>SIP Video Door Bell with Relay</b></p> <p>1.Body material: ABS plastics      2.Camera: 2M pixels with angle: 123°(H) / 69°(V) and LED White Light  3. Two Relay in and one Relay out  4. Installation: Wall-mounted  5. Water-proof &amp; Dust-proof: IP65      6. PoE (IEEE802.3af, Power-over-Ethernet);  7. Button: 1 call button with backlight  8.Two-way audio communication over IP networks with Echo Cancel  9.Complies with SIP standard for easy integration in every SIP PBX;</p>	20	US\$143	271.70
E12W		<p><b>SIP Video Door Bell with Relay &amp; Wifi</b></p> <p>1.Body material: ABS plastics      2.Camera: 2M pixels with angle: 123°(H) / 69°(V) and LED White Light  3. Two Relay in and one Relay out  4. Installation: Wall-mounted  5. Water-proof &amp; Dust-proof: IP65      6. PoE (IEEE802.3af, Power-over-Ethernet);  7. Button: 1 call button with backlight  8.Two-way audio communication over IP networks with Echo Cancel  9.Complies with SIP standard for easy integration in every SIP PBX;  <b>10. WiFi: IEEE802.11b/g/n, 2.4GHz</b></p>	20	US\$157	298.30
R20A On-Wall		<p><b>SIP Intercom with one Button (Video &amp; Card reader)</b>  <b>1.Body material: Zinc alloy</b>  2.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116o  3.RF Card Reader 13.56MHZ&amp;125KHZ Card reader  4.Output Relay: 2 output relays for door opener  5.Water-proof &amp; Dust-proof: IP65  <b>6.Installation: Surface Mount model</b>  7.PoE (IEEE802.3af, Power-over-Ethernet);  8.Two-way audio communication over IP networks with Echo Cancel  9.Complies with SIP standard for easy integration in every SIP PBX;</p>	20	US\$243	461.70
R20A In-Wall		<p><b>SIP Intercom with one Button (Video &amp; Card reader)</b>  <b>1.Body material: Zinc alloy</b>  2.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116o  3.RF Card Reader 13.56MHZ&amp;125KHZ Card reader  4.Output Relay: 2 output relays for door opener  5.Water-proof &amp; Dust-proof: IP65  <b>6.Installation: Flush Mount model</b>  7.PoE (IEEE802.3af, Power-over-Ethernet);  8.Two-way audio communication over IP networks with Echo Cancel  9.Complies with SIP standard for easy integration in every SIP PBX;</p>	20	US\$286	543.40



R20B On-wall (Two Buttons)		<p><b>SIP Intercom with TWO (2) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 2 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Surface Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$251	476.90
-------------------------------	---	---	----	---------	--------

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
R20B In-wall (Two Buttons)		<p><b>SIP Intercom with Two (2) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 2 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Flush Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$294	558.60
R20B On-wall (Three Buttons)		<p><b>SIP Intercom with Three (3) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 3 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Surface Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$257	488.30
R20B In-wall (Three Buttons)		<p><b>SIP Intercom with Three (3) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 3 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Flush Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$300	570.00
R20B On-wall (Four Buttons)		<p><b>SIP Intercom with Four (4) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 4 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Surface Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$263	499.70
R20B In-wall (Four Buttons)		<p><b>SIP Intercom with Four (4) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 4 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 7.<b>Installation: Flush Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	10	US\$306	581.40





<b>R20B On-wall (Five Buttons)</b>		<p><b>SIP Intercom with Five (5) Buttons (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      2.Camera: 2M pixels, 110°(H) / 58°(V)  3.RF Card Reader 13.56MHZ &amp; 125KHZ 4.Button: 5 call buttons with name plate 5.Output Relay: 2 output relays for door opener 6.Water-proof &amp; Dust-proof: IP65 <b>7.Installation: Surface Mount model</b>      8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	<b>10</b>	<b>US\$271</b>	<b>514.90</b>
--	---	--	-----------	----------------	---------------







Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
<b>R20B In-wall (Five Button)</b>		<p><b>SIP Intercom with Five (5) Button (Video &amp; Card reader)</b></p> <p>1.Body material: Aluminum Alloy      <b>2.Camera: 2M pixels, 110°(H) / 58°(V)</b>  <b>3.RF Card Reader 13.56MHZ &amp; 125KHZ</b>  <b>4.Button: 5 call buttons with name plate</b>  5.Output Relay: 2 output relays for door opener  6.Water-proof &amp; Dust-proof: IP65  <b>7.Installation: Flush Mount model</b>  8.PoE (IEEE802.3af, Power-over-Ethernet)  9.Two-way audio communication over IP networks with Echo Cancel 10.Complies with SIP standard for easy integration in every SIP PBX</p>	<b>10</b>	<b>US\$314</b>	<b>596.60</b>
<b>VP-R49G</b>		<p><b>Premium Android IP Video Phone, Support PoE &amp; Gigabit port</b></p> <p>1.7 inch capacitive touch screen TFT LCD, 1024*600 pixels;  2.2 M pixels CMOS camera with privacy shutter;  3. Dual switched 10/100/1000Mbps Ethernet ports, Bluetooth, USB, PoE and Wireless feature;  4. <b>Android 9.0 Operating System</b> and support Android API for the 3rd party Android application installation.</p>	<b>5</b>	<b>US\$485</b>	<b>921.50</b>



**SIP DOOR PHONE**

<b>R26C</b>		<p><b>SIP Intercom with one Button (Video &amp; Card reader)</b></p> <p>1.Body material: all-aluminum      2.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116o  3.RF Card Reader 13.56MHZ  4.Output Relay: 2 output relays for door opener  5.Water-proof &amp; Dust-proof: IP65      6.Installation: Surface Mount model      7.PoE (IEEE802.3af, Power-over-Ethernet)  8.Two-way audio communication over IP networks with Echo Cancel 9.Complies with SIP standard for easy integration in every SIP PBX</p>	<b>10</b>	<b>US\$371</b>	<b>704.90</b>
<b>R26P</b>		<p><b>SIP Intercom with one Button (Video)</b></p> <p>1.Body material: all-aluminum      2.Camera: 3M pixels, automatic lighting,Wide-angle camera: 120o  3.Output Relay: 2 output relays for door opener  4.Water-proof &amp; Dust-proof: IP65  <b>5.Installation: Surface Mount model</b>  6.PoE (IEEE802.3af, Power-over-Ethernet)  7.Two-way audio communication over IP networks with Echo Cancel 8.Complies with SIP standard for easy integration in every SIP PBX</p>	<b>10</b>	<b>US\$343</b>	<b>651.70</b>



Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
R28A		<p><b>SIP Android Door Phone with LCD</b></p> <ol style="list-style-type: none"> <li>1. <b>H.264&amp;H.265</b> video and G.722 audio codec</li> <li>2. Body material: All-aluminum</li> <li>3. <b>Display: 4.3 Inch, color TFT LCD</b></li> <li>4. <b>Camera: 2 Mega pixels, automatic lighting</b></li> <li>5. Water-proof &amp; Dust-proof: IP65</li> <li>6. Collision-proof: IK06</li> <li>7. PoE (IEEE802.3af, Power-over-Ethernet)</li> <li>8. <b>Support Wiegand, 13.56MHZ&amp;125KHZ Card reader</b></li> <li>9. Complies with SIP standard for easy integration in every SIP PBX</li> <li>10. <b>Installation: support Surface Mount and Flush Mount by using different bracket or box</b></li> </ol>	10	US\$686	1,303.40
E18C		<p><b>SIP Door Phone with Facial Recognition</b></p> <ol style="list-style-type: none"> <li>1. H.264 video and G.722 audio codec</li> <li>2. <b>Display: 7" IPS LCD capacitive touch screen 1024x600</b></li> <li>4. <b>Camera: 2 Mega pixels, WDR</b></li> <li>5. Water-proof &amp; Dust-proof: IP65</li> <li>6. PoE (IEEE802.3af, Power-over-Ethernet)</li> <li>7. <b>Support Wiegand, RS485, 125KHZ &amp; 13.56MHZ Card reader</b></li> <li>8. <b>LTE optional</b></li> <li>9. <b>Complies with SIP standard for easy integration in every SIP PBX</b></li> <li>10. <b>Installation: support Surface Mount</b></li> <li>11 <b>Body Temperature Detection (Optional)</b></li> </ol>	10	US\$800	1,520.00
R29S		<p><b>SIP Android Door Phone with Facial Recognition</b></p> <ol style="list-style-type: none"> <li>1. H.264 video and G.722 audio codec</li> <li>2. Android OS V5.1 for any 3rd party software or customization</li> <li>3. Display: 7" IPS LCD capacitive touch screen 1280x800</li> <li>4. Camera: 3 Mega pixels, automatic lighting</li> <li>5. Water-proof &amp; Dust-proof: IP65</li> <li>6. Collision-proof: IK06</li> <li>7. PoE (IEEE802.3af, Power-over-Ethernet)</li> <li>8. Support Wiegand, 13.56MHZ&amp;125KHZ Card reader</li> <li>9. Complies with SIP standard for easy integration in every SIP PBX</li> <li>10. <b>Installation: support Surface Mount and Flush Mount by using different bracket or box</b></li> </ol>	8	US\$1,214	2,306.60
R29C		<p><b>SIP Android Door Phone with Facial Recognition</b></p> <ol style="list-style-type: none"> <li>1. H.264 video and G.722 audio codec</li> <li>2. Android OS V5.1 for any 3rd party software or customization</li> <li>3. Display: 7" IPS LCD capacitive touch screen 1280x800</li> <li>4. <b>Camera: Dual camera for anti-counterfeit</b></li> <li>5. <b>Bluetooth, and Wireless feature</b></li> <li>6. Water-proof &amp; Dust-proof: IP65</li> <li>7. Collision-proof: IK06</li> <li>8. PoE (IEEE802.3af, Power-over-Ethernet)</li> <li>9. Support Wiegand, 13.56MHZ&amp;125KHZ Card reader</li> <li>10. <b>Installation: support Surface Mount and Flush Mount by using different bracket or box</b></li> </ol>	8	US\$1,500	2,850.00

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
C313S		<p><b>SIP Indoor unit (Linux Version)</b></p> <p>1.7" capacitive touch screen with energy saving mode  2.Reception of a HD picture from the door communicator  3.Two-way communication based on SIP v2.0 protocol  <b>4.Powered by PoE or external source</b> 5.Supports US or European electrical wall box mounting</p>	20	US\$129.00	245.10
C313W		<p><b>SIP Indoor unit (Linux Version)</b></p> <p>1.7" capacitive touch screen with energy saving mode  2.Reception of a HD picture from the door communicator  3.Two-way communication based on SIP v2.0 protocol  <b>4.Powered by PoE or external source</b> 5.  Supports US or European electrical wall box mounting  <b>6. Bluetooth, and Wireless feature</b></p>	20	US\$157.00	298.30
C315S		<p><b>SIP Indoor unit (Android Version)</b></p> <p><b>1.7" capacitive touch screen with energy saving mode</b>  2.Reception of a HD picture from the door communicator  3.Two-way communication based on SIP v2.0 protocol  4.Powered by PoE or external source  5.Supports US or European electrical wall box mounting</p>	20	US\$214.00	406.60
C315W		<p><b>SIP Indoor unit (Android Version)</b></p> <p><b>1.7" capacitive touch screen with energy saving mode</b>  2.Reception of a HD picture from the door communicator  3.Two-way communication based on SIP v2.0 protocol  4.Powered by PoE or external source  5.Supports US or European electrical wall box mounting</p>	20	US\$243.00	461.70
IT83A		<p><b>SIP Indoor unit (Android Version)</b></p> <p><b>1.Ultra clear, stylish and metal appearance</b>  <b>2.10" capacitive touch screen with energy saving mode</b>  3.Reception of a HD picture from the door communicator  4.Two-way communication based on SIP v2.0 protocol  5.Powered by PoE or external source  6 Supports US or European electrical wall box mounting  7.Tamper resistant design  <b>8.Camera: 1M pixels</b>  <b>9. Wifi and Bluetooth</b>  <b>10.Desktop Stand (optional)</b></p>	10	US\$557.00	1,058.30
X933S On Wall (Black/ White)		<p><b>SIP Indoor unit (Android Version)</b></p> <p><b>1. Stylish appearance from Italy</b>  <b>2. Excellent performance with Android 9.0 system</b>  3. 7-inch capacitive touch screen with energy saving mode  <b>4. Ultimate visual experience with 1280 x 800 resolution</b>  5. Reception of a HD picture from the door communicator  6. Two-way audio communication with other units in the network  7. Complies with SIP standard for easy integration in every SIP capable PBXes 8. Powered by PoE or external source  9.Support US or European electrical wall box mounting</p>	10	US\$314.00	596.60

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
X933S In Wall (White)		<p><b>SIP Indoor unit (Android Version)</b></p> <ol style="list-style-type: none"> <li>1. Stylish appearance from Italy</li> <li>2. Excellent performance with Android 9.0 system</li> <li>3. 7-inch capacitive touch screen with energy saving mode</li> <li>4. Ultimate visual experience with 1280 x 800 resolution</li> <li>5. Reception of a HD picture from the door communicator</li> <li>6. Two-way audio communication with other units in the network</li> <li>7. Complies with SIP standard for easy integration in every SIP capable PBXes</li> <li>8. Powered by PoE or external source</li> <li>9. Support US or European electrical In wall box mounting</li> </ol>	10	US\$386.00	733.40
X933W On Wall (Black/ White)		<p><b>SIP Indoor unit (Android Version)</b></p> <ol style="list-style-type: none"> <li>1. Stylish appearance from Italy</li> <li>2. Excellent performance with Android 9.0 system</li> <li>3. 7-inch capacitive touch screen with energy saving mode</li> <li>4. Ultimate visual experience with 1280 x 800 resolution</li> <li>5. Reception of a HD picture from the door communicator</li> <li>6. Two-way audio communication with other units in the network</li> <li>7. Complies with SIP standard for easy integration in every SIP capable PBXes</li> <li>8. Powered by PoE or external source</li> <li>9. Support US or European electrical wall box mounting</li> <li>10. Wifi and Bluetooth</li> </ol>	10	US\$343.00	651.70



**ACCESS CONTROL PRODUCT**

Art. No.	Picture	Description	Box	Преп. Клиент USD с ДДС	Преп. Клиент лева с ДДС
A01		<p><b>A01-RFID Access Control Terminal</b></p> <p>1.Toughened glass front panel &amp; Aluminum alloy frame                  2.13.56MHz &amp; 125kHz RFID card reader &amp; NFC                  3.20,000 card capacity &amp;100,000 event logs                  4.Support Tamper Alarm 5.Water-proof &amp; Dust-proof:IP65                  6.Installation:Wall mount &amp; Flush mount                  7.802.3af Power-over-Ethernet and 12V DC connector (if not using PoE)</p>	20	US\$170	323.00
A02		<p><b>A02-RFID+Keypad Access Control Terminal</b></p> <p>1.Touch keypad front panel &amp; Aluminum alloy frame                  2.13.56MHz &amp; 125kHz RFID card reader &amp; NFC                  3.20,000 card capacity &amp;100,000 event logs                  4.Support tamper alarm 5.Identification Mode:PIN,RFID Card,Two factor authentication                  6.Water-proof &amp; Dust-proof:IP65                  7.Installation:Wall mount &amp; Flush mount                  8.802.3af Power-over-Ethernet and 12V DC connector (if not using PoE)</p>	20	US\$200	380.00
A092S		<p><b>Smart access access controller control device with Ethernet interface</b></p> <p>1. Supports TCP/IP communication and web interface for management;                  2. Supports up to 50,000 cards and 100,000 card presenting records;                  3. Supports multi-door interlock funtion and anti-pass back function;                  4. Supports RS-485, OSDP, Wiegand protocol for accessing card reader;                  5.Supports emergency door release(EDR);                  6. Supports tamper proof alarm;                  7. Easy to establish large-scale access control system with Akuvox ACMS;                  8. Back up battery design;                  9. Power supply: 100~240VAC 50/60Hz (A092S);802.11at PoE+ (A092P)</p>	1	US\$600	1,140.00
SR01		<p><b>Compact Security Single Door I/O Module</b></p> <p>1.Installation environment: Indoor; 2.Complies with Akuvox doorphone 3.Body material: Plastic                  4.Button: 1 , for pairing 5.1 input / 1 output relay for door opener                  6.Mounting: Fits in standard installation boxes 7.Dimensions: 31x56x24mm</p>	50	US\$100.00	190.00
EC32		<p><b>Elevator Controller</b></p> <p>1. Relay Output:32                  2. Card Reader: Support wiegand 26/34                  3. Storage: 120,000 cards &amp; 200,000 events                  4. Expansion: Support to connect one expansion panel to reach 64 output                  5. Communication: TCP/IP, RS485                  6. Support working with Akuvox indoor monitor for remote elevator calling function</p>	1	US\$660	1,254.00

**ЗАБЕЛЕЖКА:**

Посочените цени са в BGN лева с начислен ДДС.

Дружеството си запазва правото да прави промени в настоящата ценова листа без предизвестие.